

Glass Splashbacks & Feature Tiles Installation Guide

Our glass splashbacks and feature tiles are made from toughened glass and designed to create a clean, striking finish. With the right preparation and adhesive, they're straightforward to install and suitable for confident DIYers or professional installers.

Before you start

Before fitting, check that the wall surface is:

- Clean and dry
- Free from dust, grease or debris
- Relatively even, with no large bumps or deep hollows

Walls do **not** need to be perfectly flat. Small variations can be adjusted for during installation by varying the amount of adhesive used.

Adhesive

Both glass splashbacks and feature tiles should be fixed using a:

Neutral, clear, solvent-free, low-modulus silicone
(often referred to as *mirror adhesive*)

This type of adhesive allows for slight movement and provides strong, even support for glass.

Installing glass splashbacks

1. Prepare the splashback

- Lay the splashback **glossy side down** on a towel or blanket to protect the surface

2. Apply adhesive

- Apply equally sized blobs of adhesive to the back of the splashback
- Each blob should be roughly **20mm in diameter**
- Space blobs approximately **100mm apart**

Avoid placing adhesive blobs too close to the edges, as the silicone may squeeze out once pressed against the wall.

3. Fix to the wall

- Carefully lift the splashback into position
- Press it gently but firmly against the wall, applying even pressure across the whole panel

If any areas feel uneven or “bouncy”:

- Remove the splashback
- Add a little more adhesive where needed
- Reposition and press again

4. Sealing

Once the splashback has had time to settle:

- Run a neat bead of silicone around the edges
- Lightly spray with warm soapy water
- Smooth with a finger to remove excess and create a clean, even seal

Installing glass Feature Tiles

Glass Feature Tiles are installed in much the same way as splashbacks.

1. Wall preparation

- Ensure the wall is clean and free of large bumps or hollows
- Small uneven areas can be compensated for by varying the amount of adhesive behind each tile

2. Applying adhesive

- Place tiles on a towel or blanket while applying adhesive
- Apply silicone to the back of each tile
- Position tiles on the wall and press gently into place

Tile spacers can be used to keep tiles evenly spaced while the adhesive sets.

3. Grouting

Once the tiles have fully settled and dried:

- Apply a **normal solvent-free grout** using a soft squeegee
- Clean off excess grout with clean warm water, as you would with standard tiles

Important note on cutting

All of our splashbacks and feature tiles are made from **toughened (tempered) glass**.

- Toughened glass **cannot be cut or trimmed**
- If you need a different size, shape or cut-out, please let us know **before ordering**

Need help?

If you have any questions about installation or preparation, we're always happy to help:

sayhello@forthefloorandmore.com

customer.help@forthefloorandmore.com